

ISO/IEC JTC 1/SC 34

Date: 2005-12-16

ISO/IEC FCD 13250-3

ISO/IEC JTC 1/SC 34/WG 3

Secretariat: SCC

Information Technology — Topic Maps — Part 3: XML Syntax

Warning

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 · CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Syntax	1
4.1 General	2
4.2 Common declarations	2
4.3 The topicMap element	2
4.4 The topic element	2
4.5 The itemIdentity element	3
4.6 The subjectLocator element	3
4.7 The subjectIdentifier element	3
4.8 The topicName element	3
4.9 The value element	3
4.10 The variant element	3
4.11 The scope element	4
4.12 The instanceOf element	4
4.13 The occurrence element	4
4.14 The resourceData element	4
4.15 The resourceRef element	4
4.16 The association element	5
4.17 The role element	5
4.18 The topicRef element	5
4.19 The mergeMap element	5
5 Deserialization	5
5.1 General	5
5.2 The topicMap element	6
5.3 The topic element	6
5.4 The itemIdentity element	6
5.5 The subjectLocator element	6
5.6 The subjectIdentifier element	6
5.7 The topicName element	7
5.8 The value element	7
5.9 The variant element	7
5.10 The resourceRef element	7
5.11 The resourceData element	7
5.11.1 General	7
5.11.2 Canonicalizing embedded XML	7
5.12 The scope element	8
5.13 The instanceOf element	8
5.14 The occurrence element	8
5.15 The association element	8
5.16 The role element	8
5.17 The mergeMap element	9
5.18 Common processing rules	9
5.18.1 General	9
5.18.2 Creating IRIs for reference elements	9
5.18.3 Creating IRIs from strings	9
5.18.4 Processing the reifier attribute	9
5.18.5 Producing topics from topicRef elements	9
6 Conformance	10
Annex A (normative) A RELAX-NG schema for XTM 1.1	11

Annex B (informative) The XTM 1.1 DTD	13
Annex C (informative) An XML Schema schema for XTM 1.1	16
Annex D (informative) Serialization	20
Annex E (informative) Differences with XTM 1.0	21
Annex F (informative) Subject identifiers for defined terms	22
Bibliography	23

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

ISO/IEC 13250-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information Technology*, Subcommittee SC 34, Document Description and Processing Languages.

ISO/IEC 13250 consists of the following parts, under the general title *Information Technology — Topic Maps*:

- *Part 1: Overview and Basic Concepts*
- *Part 2: Data Model*
- *Part 3: XML Syntax*
- *Part 4: Canonicalization*
- *Part 5: Reference Model*

Introduction

XTM (XML Topic Maps) 1.1 is a syntax for the interchange of Topic Maps. The syntax is not designed to be extended or modified. Ease of human authoring was not prioritized during the design of XTM, and consequently it is not recommended to edit the syntax directly.

This part of ISO/IEC13250 should be read in conjunction with *[ISO/IEC 13250-2]* since the interpretation of the XTM syntax is defined through a mapping from the syntax to the data model there defined. Informative guidance on how to serialize instances of the data model to the XTM syntax is also provided.

XTM 1.1 is a revision of the XTM 1.0 syntax defined in *[ISO/IEC 13250:2003]* and *[XTM1.0]*. A description of the differences between the two versions can be found in Annex E.

Information Technology — Topic Maps — Part 3: XML Syntax

1 Scope

This part of ISO/IEC13250 defines an XML-based interchange syntax for Topic Maps, which can be used to interchange instances of the data model defined in [ISO/IEC 13250-2]. It also defines a mapping from the interchange syntax to the data model. The syntax is defined with a RELAX-NG schema, and more precision is provided through the mapping to the data model, which effectively also defines the interpretation of the syntax.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE Each of the following documents has a unique identifier that is used to cite the document in the text. The unique identifier consists of the part of the reference up to the first comma.

ISO/IEC 13250-2, *Topic Maps — Data Model*, available at <<http://www.isotopicmaps.org/sam/>>

W3C XML, *Extensible Markup Language (XML) 1.0 (Third Edition)*, W3C Recommendation, 4 February 2004, available at <<http://www.w3.org/TR/2004/REC-xml-20040204>>

W3C XML-Names, *Namespaces in XML*, W3C Recommendation, 14 January 1999, available at <<http://www.w3.org/TR/1999/REC-xml-names-19990114/>>

W3C XPointer, *XPointer Framework Version 1.0*, W3C Recommendation, 25 March 2003, available at <<http://www.w3.org/TR/2003/REC-xptr-framework-20030325/>>

W3C XML-Infoset, *XML Information Set (Second Edition)*, W3C Recommendation, 4 February 2004, available at <<http://www.w3.org/TR/2004/REC-xml-infoset-20040204>>

W3C Canonical XML, *Canonical XML Version 1.0*, W3C Recommendation, 15 March 2001, available at <<http://www.w3.org/TR/2001/REC-xml-c14n-20010315>>

ISO/IEC 19757-2, *Document Schema Definition Languages (DSDL) — Part 2: Grammar-based validation — RELAX NG*, available at <<http://www.relaxng.org>>

IETF RFC 3986, *Uniform Resource Identifiers (URI): Generic Syntax*, Internet Standards Track Specification, January 2005, available at <<http://www.ietf.org/rfc/rfc3986.txt>>

IETF RFC 3987, *Internationalized Resource Identifiers (IRIs)*, Internet Standards Track Specification, January 2005, available at <<http://www.ietf.org/rfc/rfc3987.txt>>

3 Terms and definitions

For the purposes of this part of ISO/IEC13250, the following terms and definitions apply.

3.1 XTM

the syntax defined in this part of ISO/IEC13250

4 Syntax

4.1 General

The acronym *XTM* is often used to refer to the syntax defined in this part of ISO/IEC13250. Its full name is XML Topic Maps. An XTM document is an XML document that conforms to the XTM syntax. This clause defines the syntax of XTM documents using prose and a RELAX-NG schema in compact syntax [ISO/IEC 19757-2]. The full schema can be found in Annex A, a DTD in Annex A, and a W3C XML Schema in Annex A.

4.2 Common declarations

The following declarations are used throughout the schema for brevity.

```
default namespace = "http://www.topicmaps.org/xtm/"
namespace xtm = "http://www.topicmaps.org/xtm/"

datatypes xsd = "http://www.w3.org/2001/XMLSchema-datatypes"

start = topicMap

id = attribute id { xsd:ID }
reifiable = attribute reifier { xsd:anyURI }?, itemIdentity*

href = attribute href { xsd:anyURI }

any-markup = (text | element * - xtm:* { attribute * { text }*, any-markup* })*
```

All href attributes shall contain IRIs valid according to [IETF RFC 3986] and [IETF RFC 3987].

4.3 The topicMap element

The topicMap element type is the document element of all XTM documents. It acts as a container for the topic map, and can be used to reify it, but has no further significance.

The topicMap element type is declared as follows:

```
topicMap = element topicMap { reifiable, version, mergeMap*,
    (topic | association)* }

version = attribute version { "1.1" }
```

The attributes have the following meanings:

reifier

If present, a reference to the topic which reifies the topic map. The reference is an IRI.

version

The version of the XTM syntax to which the document conforms. For XTM 1.1 documents this shall be "1.1".

4.4 The topic element

The topic element type is used to represent topics, and acts as a container and point of reference for topic information. The child elements of the topic element provide some topic characteristic assignments, as well as other properties, while association roles played by the topic are specified outside the topic element.

The topic element type is declared as follows:

```
topic = element topic { id,
    (itemIdentity | subjectLocator | subjectIdentifier)*,
    instanceOf*, (topicName | occurrence)* }
```


The id attribute provides a unique identifier for the topic, which is used to refer to it. It is mapped to an item identifier in the model.

4.5 The itemIdentity element

The itemIdentity element is used to assign an item identifier to the topic map construct represented by its parent element.

The itemIdentity element is declared as follows:

```
itemIdentity = element itemIdentity { href }
```

The href attribute contains the item identifier as an absolute or relative IRI.

4.6 The subjectLocator element

The subjectLocator element is used to assign a subject locator to the topic that is represented by its parent topic element.

The subjectLocator element is declared as follows:

```
subjectLocator = element subjectLocator { href }
```

The href attribute contains the subject locator as an absolute or relative IRI.

4.7 The subjectIdentifier element

The subjectIdentifier element is used to assign a subject identifier to the topic that is represented by its parent topic element.

The subjectIdentifier element is declared as follows:

```
subjectIdentifier = element subjectIdentifier { href }
```

The href attribute contains the subject identifier as an absolute or relative IRI.

4.8 The topicName element

The topicName element type is used to add topic names to the topic represented by the parent topic element. The child elements of the topicName element provide the property values of the topic name item.

The topicName element type is declared as follows:

```
topicName = element topicName { reifiable, instanceOf, scope?, value, variant* }
```

The reifier attribute contains a reference to the topic which reifies the topic name. The reference is an IRI.

4.9 The value element

The value element type is used to provide the value of the topic name.

The value element type is declared as follows:

```
value = element value { text }
```

4.10 The variant element

The variant element type is used to add a variant name to a topic name.

The variant element type is declared as follows:

```
variant = element variant { reifiable, scope, (resourceRef | resourceData) }
```

The reifier attribute contains a reference to the topic which reifies the variant name. The reference is an IRI.

4.11 The scope element

The scope element type is used to assign scope to the topic map construct represented by the parent element.

The scope element type is declared as follows:

```
scope = element scope { topicRef+ }
```

The id attribute is ignored during deserialization.

4.12 The instanceOf element

The instanceOf element type is used to assign a type to the topic map construct represented by its parent element. The type is always a topic, indicated by the instanceOf element's child element.

The instanceOf element type is declared as follows:

```
instanceOf = element instanceOf { topicRef }
```

The id attribute is ignored during deserialization.

4.13 The occurrence element

The occurrence element type is used to assign an occurrence to the topic defined by the parent element.

The occurrence element type is declared as follows:

```
occurrence = element occurrence { reifiable,  
instanceOf, scope?, ( resourceRef | resourceData ) }
```

The reifier attribute contains a reference to the topic which reifies the occurrence. The reference is an IRI.

4.14 The resourceData element

The resourceData element type represents an information resource in the form of content contained within the XTM document. This information resource may be either a variant name or an occurrence, and it can have a datatype.

The resourceData element type is declared as follows:

```
datatype = attribute datatype { xsd:anyURI }  
  
resourceData = element resourceData { datatype?, any-markup }
```

The datatype attribute contains an IRI identifying the datatype of the resource that is represented by the resourceData element.

4.15 The resourceRef element

The resourceRef element type refers to an information resource. The information resource can be an occurrence, if the parent element is occurrence, or a variant name, if the parent element is variant.

The resourceRef element type is declared as follows:

resourceRef = element resourceRef { href }

The href attribute contains an absolute or relative IRI referring to the information resource.

4.16 The association element

The association element type represents associations. The role child elements provide the association roles of the association.

The association element type is declared as follows:

association = element association { reifiable, instanceOf, scope?, role+ }

The reifier attribute contains a reference to the topic which reifies the association. The reference is an IRI.

4.17 The role element

The role element type is used to assign an association role to the association created by the association parent element.

The role element type is declared as follows:

role = element role { reifiable, instanceOf, topicRef }

The reifier attribute contains a reference to the topic which reifies the association role. The reference is an IRI.

4.18 The topicRef element

The topicRef element type refers to a topic, either within the same XML document or externally. The significance of the reference depends on the context; for detailed descriptions of the different cases, see Clause 5.

The topicRef element type is declared as follows:

topicRef = element topicRef { href }

The href attribute contains the IRI reference that is the topic reference. This IRI reference shall have a fragment identifier which shall be what *[W3C XPointer]* calls a shorthand pointer (formerly barename).

4.19 The mergeMap element

The mergeMap element type refers to an external XTM document that is to be merged into the topic map that contains the mergeMap element.

The mergeMap element type is declared as follows:

mergeMap = element mergeMap { href }

The href attribute contains an absolute or relative IRI referring to the XTM document that is to be merged in. The IRI shall not have a fragment identifier.

5 Deserialization

5.1 General

The process of exporting Topic Maps from an implementation's internal representation of the data model to an instance of a Topic Maps syntax is known as serialization. The opposite process, deserialization, is the process of building an instance of an implementation's internal representation of the data model from an instance of a Topic Maps syntax.

This clause defines how instances of the XTM syntax are deserialized into instances of the data model defined in [ISO/IEC 13250-2]. Serialization is only implicitly defined, although some guidance can be found in Annex A.

The input to the deserialization process is:

- A document item as defined by [W3C XML-Infoset], representing an XTM document. (Information item properties from [W3C XML-Infoset] are referred to using [[property name]], in order to distinguish them from properties from [ISO/IEC 13250-2].)
- An absolute IRI. This is the IRI from which the XTM document was retrieved, known as the document IRI. This IRI shall always be provided, as it is necessary in order to assign the item identifiers of the topic items created during deserialization. If the XML document was not read from any particular IRI the application is responsible for providing an IRI considered suitable.

Deserialization is done by processing each element item in the document item in document order. For each element item encountered the operations specified in the clause for that element type are performed. An input element item matches a clause in this document when the [[namespace uri]] property is set to "http://www.topicmaps.org/xtm/", and the [[local name]] matches the element type name given in that section's title.

Whenever a new information item is created, those of its properties which have set values are initialized to the empty set; all other properties are initialized to null.

NOTE This part of ISO/IEC13250 requires an instance of the XML Information Set as input to the deserialization process, but in most cases the actual input will be an XML document. This part of ISO/IEC13250 does not constrain how XML Information Set instances are built from XML documents, but assumes that in most cases this will be done by simply using an XML processor.

XML processors conformant to the XML Recommendation may produce different results given the same XML document, depending on whether they are validating or non-validating, and depending on which optional features they support. Reliance on any particular behaviour in the XML processors used by recipients is strongly discouraged.

5.2 The topicMap element

The topicMap element causes a topic map item to be created. If the reifier attribute is present, it is processed according to the procedure given in 5.18.4.

5.3 The topic element

The topic element causes a topic item to be created and inserted into the [topics] property of the topic map item.

A locator is created by concatenating the document IRI, a "#" character, and the value of the [[normalized value]] property of the attribute item in the [[attributes]] property of that element item whose [[local name]] property is "id". This locator is added to the [item identifiers] property of the topic item.

5.4 The itemIdentity element

The itemIdentity element causes a locator to be created from its href attribute as specified in 5.18.2. This locator is added to the [item identifiers] property of the information item created by the parent element.

5.5 The subjectLocator element

The subjectLocator element causes a locator to be created from its href attribute as specified in 5.18.2. This locator is added to the [subject locators] property of the topic item created by the parent topic element.

5.6 The subjectIdentifier element

The subjectIdentifier element causes a locator to be created from its href attribute as specified in 5.18.2. This locator is added to the [subject identifiers] property of the topic item created by the parent topic element.

5.7 The topicName element

The topicName element causes a topic name item to be created, and added to the [topic names] property of the topic item created by the parent topic element.

If the topicName element has an instanceOf child element it is processed according to the procedure in 5.13. Otherwise the [type] property of the topic name item is set to the topic item whose [subject identifiers] property contains "http://psi.topicmaps.org/iso13250/model/topic-name"; if no such topic item exists, one is created.

If the reifier attribute is present, it is processed according to the procedure given in 5.18.4.

5.8 The value element

The information items in the [[children]] property of the value element are traversed, and for each character information item the Unicode character specified by the [[character code]] property is appended to the [value] property of the topic name item created by the parent topicName element.

5.9 The variant element

The variant element causes a variant item to be created and added to the [variants] property of the topic name item created by the topicName parent element.

After the scope child element has been processed, the topics in the [scope] property of the topic name item created by the topicName parent element are added to the [scope] property of the variant name.

If the reifier attribute is present, it is processed according to the procedure given in 5.18.4.

5.10 The resourceRef element

The resourceRef element causes a locator to be produced following the procedure in 5.18.2 and inserted into the [value] property of the information item created by the parent element. The [datatype] property of the information item is also set to "http://www.w3.org/2001/XMLSchema#anyURI".

5.11 The resourceData element

5.11.1 General

The resourceData element sets the [value] property of the information item created by the parent element. If the datatype attribute is not present the [datatype] property is set to "http://www.w3.org/2001/XMLSchema#string"; if the attribute is present the [datatype] property is set to the value of the attribute.

If the [datatype] property is set to "http://www.w3.org/2001/XMLSchema#any" the procedure in 5.11.2 is followed.

If the [datatype] property is set to "http://www.w3.org/2001/XMLSchema#anyURI" the procedure in 5.18.3 is followed to produce the value of the [value] property from the content of the resourceData element.

Otherwise the information items in the [[children]] property of the element item are traversed, and for each character information item the Unicode character specified by the [[character code]] property is added to the [value] property of the variant item created by the parent variant element. In this case it is an error for the resourceData element to have child elements.

5.11.2 Canonicalizing embedded XML

XTM documents may contain arbitrary markup inside resourceData elements, and this markup is represented in the data model as a string. This section describes the string representation of embedded markup.

A string representation is produced from the embedded markup by applying the canonicalization process described in *[W3C Canonical XML]*. The input to the canonicalization process is an XPath node set (as *[W3C Canonical XML]* requires this). The node set is produced as described below:

- Add XPath nodes for all element, attribute, and character information items that are descendants of the `resourceData` element.
- Remove all namespace nodes attached to these element nodes where there is not at least one element or attribute node in the set with this namespace IRI and namespace prefix.

The second parameter to the canonicalization process is false (that is, comments are not included).

NOTE The output of the *[W3C Canonical XML]* is defined as a UTF-8-encoded octet sequence, but the output of the process defined above should be the equivalent string.

5.12 The scope element

The scope element has no direct effect on the information set being produced, but changes the interpretation of its child elements. Each `topicRef` child element is processed according to the procedure in 5.18.5 to produce a topic item. These topic items are gathered into a set that is assigned as the value of the `[scope]` property of the information item produced by the parent element.

5.13 The instanceOf element

The `instanceOf` element has no direct effect on the information set being produced, but changes the interpretation of its child elements. The exact interpretation depends on the parent element of the `instanceOf` element, however.

Regardless of what parent element the `instanceOf` element is found in, the child element produces a topic item following the procedure in 5.18.5.

If the parent element is a `topicName`, `occurrence`, `association`, or `role` element, the produced topic item is set as the value of the `[type]` property of the information item produced by the parent element.

If the parent element is a topic element a new association item is created, with two association role items in its `[roles]` property, and a topic item representing the type-instance association type (described in *[ISO/IEC 13250-2]*, 7.2) in its `[type]` property. If no such topic item exists already, one is created, and the subject identifier added to its `[subject identifiers]` property.

The first association role item has its `[type]` property set to the topic item representing the type role in the same association (see the section referenced above), while the `[player]` property is set to the topic produced by the child element.

The second association role item has its `[type]` property set to the topic item representing the instance role in the same association (see the section referenced above), while the `[player]` property is set to the topic produced by the parent element (that is, the current topic).

5.14 The occurrence element

The occurrence element causes an occurrence item to be created and added to the `[occurrences]` property of the topic item created by the parent topic element.

If the `reifier` attribute is present, it is processed according to the procedure given in 5.18.4.

5.15 The association element

The association element causes an association item to be created, and added to the `[associations]` property of the topic map item.

If the `reifier` attribute is present, it is processed according to the procedure given in 5.18.4.

5.16 The role element

The role element causes an association role item to be created, and added to the [roles] property of the association item created by the parent association element.

The topicRef child element is resolved to a topic according to the procedure in 5.18.5, and that topic is set as the value of the [player] property of the association role item.

If the reifier attribute is present, it is processed according to the procedure given in 5.18.4.

5.17 The mergeMap element

An absolute IRI is produced from the mergeMap element's href attribute, following the procedure in 5.18.2. It is an error if this IRI contains a fragment identifier.

The IRI of the external information resource is resolved and the resource is parsed with an XML processor according to [W3C XML] to produce an XML Information Set according to [W3C XML-Infoset]. It is an error if the resource is not a well-formed XML document. The XML Information Set is then deserialized into a data model instance using the procedure in Clause 5 with the document item and the IRI of the information resource as input.

The new data model instance (B) is then merged into the current one (A) by:

- Adding all topic items in B's [topics] property to A's [topics] property.
- Adding all association items in B's [associations] property to A's [associations] property.

NOTE Adding topics and associations to A may trigger further merges, as described in [ISO/IEC 13250-2].

5.18 Common processing rules

5.18.1 General

This clause defines common processing rules used throughout this part of ISO/IEC13250. The rules are referenced from the clauses to which they apply.

5.18.2 Creating IRIs for reference elements

Creation of a IRI from an element information item in the XML Infoset representing a reference is done by locating the attribute information item in the element's [[attributes]] property whose [[local name]] property is "href". The value of that attribute information item's [[normalized value]] property is turned into an absolute IRI following the procedure in 5.18.3.

5.18.3 Creating IRIs from strings

To create an IRI from a string unescape the string by replacing %HH escape sequences with the characters they represent, and decode the resulting character sequence from UTF-8 to a sequence of abstract Unicode characters. The resulting string is turned into an absolute IRI by resolving it against the document IRI.

5.18.4 Processing the reifier attribute

The value in the [[normalized value]] property of the attribute node representing the reifier attribute is resolved into an absolute IRI following the procedure in 5.18.3. If there is a topic item with that IRI in its [item identifiers] property, that topic item is set as the value of the [reifier] property of the topic map construct being processed. If no such topic item exists, a new topic item is created, the IRI added to its [item identifiers] property, and that topic item is set as the value of the [reifier] property of the topic map construct being processed.

5.18.5 Producing topics from topicRef elements

From the topicRef element a locator is produced according to the rules in 5.18.2. If the data model has a topic item whose [subject identifiers] or [item identifiers] properties contain an equal locator that topic item is the one produced by this topicRef element.

If no such topic item exists, a topic item is created, and the locator added to its [item identifiers] property. That topic item is then the one produced by this topicRef element.

6 Conformance

An XTM document conforms to this part of ISO/IEC13250 provided it:

- Is a well-formed XML document [*W3C XML*].
- Conforms to [*W3C XML-Names*].
- Conforms to the schema in Annex A.
- Is deserializable according to the procedure defined in Clause 5 without causing any errors or violating any data model constraints.

An XTM processor conforms to this part of ISO/IEC13250 provided it meets all the requirements given below.

- The XTM processor shall reject any input which is not a conforming XTM document.
- The XTM processor shall produce a representation that is isomorphic to the data model instance created by the procedure given in Clause 5 for all XTM documents.

Annex A (normative)

A RELAX-NG schema for XTM 1.1

```
# =====
#
# XML Topic Maps 1.1
#
# This is the normative RELAX-NG schema for the XTM 1.1 syntax, as
# defined in ISO 13250-3.
#
# See http://www.isotopicmaps.org/sam/sam-xtm/
#
# =====

# --- Common declarations

default namespace = "http://www.topicmaps.org/xtm/"
namespace xtm = "http://www.topicmaps.org/xtm/"

datatypes xsd = "http://www.w3.org/2001/XMLSchema-datatypes"

start = topicMap

id = attribute id { xsd:ID }
reifiable = attribute reifier { xsd:anyURI }?, itemIdentity*

href = attribute href { xsd:anyURI }

any-markup = (text | element * - xtm:* { attribute * { text }*, any-markup* })*

# --- The schema

topicMap = element topicMap { reifiable, version, mergeMap*,
                             (topic | association)* }

version = attribute version { "1.1" }

topic = element topic { id,
                       (itemIdentity | subjectLocator | subjectIdentifier)*,
                       instanceOf*, (topicName | occurrence)* }

topicName = element topicName { reifiable, instanceOf?, scope?, value, variant* }

value = element value { text }

variant = element variant { reifiable, scope, (resourceRef | resourceData) }

scope = element scope { topicRef+ }

instanceOf = element instanceOf { topicRef }

occurrence = element occurrence { reifiable,
```

```
instanceOf, scope?, ( resourceRef | resourceData ) }

datatype = attribute datatype { xsd:anyURI }

resourceData = element resourceData { datatype?, any-markup }

association = element association { reifiable, instanceOf, scope?, role+ }

role = element role { reifiable, instanceOf, topicRef }

topicRef = element topicRef { href }
resourceRef = element resourceRef { href }
subjectLocator = element subjectLocator { href }
subjectIdentifier = element subjectIdentifier { href }
itemIdentity = element itemIdentity { href }

mergeMap = element mergeMap { href }

# --- End of schema
```

Annex A (informative)

The XTM 1.1 DTD

```

<!-- ..... -->
<!-- XML Topic Map DTD ..... -->

<!-- XML Topic Map (XTM) DTD, Version 1.1

This is XTM 1.1, an XML interchange syntax for ISO 13250 Topic
Maps, defined by ISO 13250-3.

Use this URI to identify the default XTM namespace:

"http://www.topicmaps.org/xtm/"

The formal public identifier for this DTD is:

"ISO/IEC 13250-3:2005//DTD XML Topic Maps (XTM) 1.1//EN"

See http://www.isotopicmaps.org/sam/sam-xtm/

-->

<!-- topicMap ..... -->

<!ELEMENT topicMap
  ( itemIdentity*, mergeMap*, ( topic | association )* )
>
<!ATTLIST topicMap
  version      CDATA   #FIXED '1.1'
  xmlns        CDATA   #FIXED 'http://www.topicmaps.org/xtm/'
  reifier      CDATA   #IMPLIED
>

<!-- topic ..... -->

<!ELEMENT topic
  ( ( itemIdentity | subjectLocator | subjectIdentifier )*,
    instanceOf*, ( topicName | occurrence )* )
>
<!ATTLIST topic
  id           ID      #IMPLIED
>

<!-- itemIdentity ..... -->

<!ELEMENT itemIdentity
  EMPTY
>
<!ATTLIST itemIdentity
  href         CDATA   #REQUIRED
>

<!-- subjectLocator..... -->

```

```

<!ELEMENT subjectLocator
  EMPTY
>
<!ATTLIST subjectLocator
  href      CDATA   #REQUIRED
>

<!-- subjectIdentifier..... -->

<!ELEMENT subjectIdentifier
  EMPTY
>
<!ATTLIST subjectIdentifier
  href      CDATA   #REQUIRED
>

<!-- topicName ..... -->

<!ELEMENT topicName
  ( itemIdentity*, instanceOf?, scope?, value, variant* )
>
<!ATTLIST topicName
  reifier    CDATA   #IMPLIED
>

<!-- value ..... -->

<!ELEMENT value ( #PCDATA ) >

<!-- variant ..... -->

<!ELEMENT variant
  ( itemIdentity*, scope, ( resourceRef | resourceData ) )
>
<!ATTLIST variant
  reifier    CDATA   #IMPLIED
>

<!-- scope ..... -->

<!ELEMENT scope
  ( topicRef )+
>

<!-- instanceOf ..... -->

<!ELEMENT instanceOf
  ( topicRef )
>

<!-- occurrence ..... -->

<!ELEMENT occurrence
  ( itemIdentity*, instanceOf, scope?, ( resourceRef | resourceData ) )
>
<!ATTLIST occurrence
  reifier    CDATA   #IMPLIED
>

```

```

<!-- resourceData ..... -->

<!ELEMENT resourceData
  ANY
>
<!ATTLIST resourceData
  datatype    CDATA    #IMPLIED
>

<!-- resourceRef ..... -->

<!ELEMENT resourceRef
  EMPTY
>
<!ATTLIST resourceRef
  href        CDATA    #REQUIRED
>

<!-- association ..... -->

<!ELEMENT association
  ( itemIdentity*, instanceOf, scope?, role+ )
>
<!ATTLIST association
  reifier     CDATA    #IMPLIED
>

<!-- role ..... -->

<!ELEMENT role
  ( itemIdentity*, instanceOf, topicRef )
>
<!ATTLIST role
  reifier     CDATA    #IMPLIED
>

<!-- topicRef ..... -->

<!ELEMENT topicRef
  EMPTY
>
<!ATTLIST topicRef
  href        CDATA    #REQUIRED
>

<!-- mergeMap ..... -->

<!ELEMENT mergeMap
  EMPTY
>
<!ATTLIST mergeMap
  href        CDATA    #REQUIRED
>

<!-- end of XML Topic Map (XTM) 1.1 DTD -->

```

Annex A (informative)

An XML Schema schema for XTM 1.1

```

<!-- ..... -->
<!-- XML Topic Map Schema ..... -->

<!-- XML Topic Map (XTM) Schema, Version 1.1

    This is XTM 1.1, an XML interchange syntax for ISO 13250 Topic
    Maps, defined by ISO 13250-3.

    See http://www.isotopicmaps.org/sam/sam-xtm/

-->
<xs:schema targetNamespace="http://www.topicmaps.org/xtm/"
  elementFormDefault="qualified"
  xmlns="http://www.topicmaps.org/xtm/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:dc="http://purl.org/dc/elements/1.1/">
  <xs:annotation>
    <xs:appinfo>
      <dc:title>W3C XML Schema for XTM 1.1</dc:title>
      <dc:owner>ISO/IEC JTC1 SC34</dc:owner>
      <dc:contributor>Max Voskob</dc:contributor>
      <dc:contributor>Lars Marius Garshol</dc:contributor>
      <dc:contributor>Ann Wrightson</dc:contributor>
    </xs:appinfo>
  </xs:annotation>

  <!-- any-markup .....-->
  <xs:complexType name="any-markup" mixed="true">
    <xs:complexContent mixed="true">
      <xs:restriction base="xs:anyType">
    </xs:restriction>
  </xs:complexContent>
  </xs:complexType>

  <xs:sequence>
    <xs:any namespace="##other" processContents="lax" minOccurs="0"
      maxOccurs="unbounded"/>
  </xs:sequence>

  <xs:attribute name="datatype" type="xs:anyURI"/>
  </xs:attribute>

  <!-- topicMap ..... -->
  <xs:element name="topicMap">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element ref="mergeMap" minOccurs="0" maxOccurs="unbounded"/>
        <xs:choice minOccurs="0" maxOccurs="unbounded">
          <xs:element ref="topic"/>
          <xs:element ref="association"/>
        </xs:choice>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:attribute name="reifier" type="xs:anyURI"/>

```

```

    <xs:attribute name="version" fixed="1.1"/>
  </xs:complexType>
</xs:element>

<!-- topic ..... -->
<xs:element name="topic">
  <xs:complexType>
    <xs:sequence>
      <xs:choice minOccurs="0" maxOccurs="unbounded">
        <xs:element ref="itemIdentity"/>
        <xs:element ref="subjectLocator"/>
        <xs:element ref="subjectIdentifier"/>
      </xs:choice>
      <xs:element ref="instanceOf" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element ref="topicName"/>
      <xs:element ref="occurrence"/>
    </xs:choice>
  </xs:complexType>
  <xs:attribute name="id" type="xs:ID" use="required"/>
</xs:element>

<!-- itemIdentity ..... -->
<xs:element name="itemIdentity">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>

<!-- subjectLocator ..... -->
<xs:element name="subjectLocator">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>

<!-- subjectIdentifier ..... -->
<xs:element name="subjectIdentifier">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>

<!-- topicName ..... -->
<xs:element name="topicName">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:element ref="instanceOf" minOccurs="0"/>
    <xs:element ref="scope" minOccurs="0"/>
    <xs:element ref="value"/>
    <xs:element ref="variant" minOccurs="0" maxOccurs="unbounded"/>
  </xs:complexType>
  <xs:attribute name="reifier" type="xs:anyURI"/>
</xs:element>

<!-- value ..... -->
<xs:element name="value" type="xs:string"/>

```

```

<!-- variant ..... -->
<xs:element name="variant">
  <xs:complexType>
    <xs:sequence>
<xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="scope"/>
      <xs:choice>
        <xs:element ref="resourceData"/>
        <xs:element ref="resourceRef"/>
      </xs:choice>
    </xs:sequence>
    <xs:attribute name="reifier" type="xs:anyURI"/>
  </xs:complexType>
</xs:element>

<!-- scope ..... -->
<xs:element name="scope">
  <xs:complexType>
    <xs:choice>
<xs:element ref="topicRef" maxOccurs="unbounded"/>
    </xs:choice>
  </xs:complexType>
</xs:element>

<!-- instanceOf ..... -->
<xs:element name="instanceOf">
  <xs:complexType>
    <xs:choice>
<xs:element ref="topicRef"/>
    </xs:choice>
  </xs:complexType>
</xs:element>

<!-- occurrence ..... -->
<xs:element name="occurrence">
  <xs:complexType>
    <xs:sequence>
<xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="instanceOf"/>
<xs:element ref="scope" minOccurs="0"/>
    <xs:choice>
      <xs:element ref="resourceRef"/>
      <xs:element ref="resourceData"/>
    </xs:choice>
    </xs:sequence>
    <xs:attribute name="reifier" type="xs:anyURI"/>
  </xs:complexType>
</xs:element>

<!-- resourceData ..... -->
<xs:element name="resourceData" type="any-markup">

<!-- association ..... -->
<xs:element name="association">
  <xs:complexType>
    <xs:sequence>
<xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="instanceOf"/>
<xs:element ref="scope" minOccurs="0"/>

```



```

<xs:element ref="role" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="reifier" type="xs:anyURI"/>
</xs:complexType>
</xs:element>

<!-- role ..... -->
<xs:element name="role">
  <xs:complexType>
    <xs:sequence>
<xs:element ref="itemIdentity" minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="instanceOf"/>
      <xs:element ref="topicRef"/>
    </xs:sequence>
    <xs:attribute name="reifier" type="xs:anyURI"/>
  </xs:complexType>
</xs:element>

<!-- topicRef ..... -->
<xs:element name="topicRef">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>

<!-- resourceRef ..... -->
<xs:element name="resourceRef">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>

<!-- mergeMap ..... -->
<xs:element name="mergeMap">
  <xs:complexType>
    <xs:attribute name="href" type="xs:anyURI" use="required"/>
  </xs:complexType>
</xs:element>
</xs:schema>

```

Annex A (informative)

Serialization

This section provides information on how to serialize data model instances using the XTM syntax. The main text of this part of ISO/IEC13250 already provides the constraints necessary to ensure interoperability, but as serialization is not entirely straightforward, this section provides additional guidance for implementors.

Generally, a serialization implementation should guarantee that for any data model instance the XTM serialization produced by the implementation should when deserialized to a new data model instance produce one that has the same canonicalization as the original data model instance, according to *[ISO 13250-4]*.

Annex A (informative)

Differences with XTM 1.0

This annex describes the differences between the syntax defined in this edition of ISO 13250 and that given in *[ISO/IEC 13250:2003]*.

The differences are:

- The namespace URI has changed.
- The version attribute has been added to the topicMap element.
- The parameters element has been replaced by scope.
- The roleSpec element has been replaced by instanceOf.
- The member element has been replaced by role.
- A single topic reference is now required as the child of role.
- The baseName element has been replaced by topicName.
- The instanceOf element is now allowed inside topicName.
- The variantName and subjectIdentity elements have been removed.
- The variant element can no longer be nested.
- The instanceOf element is now required inside occurrence, association, and role.
- The mergeMap element no longer supports added scope.
- The id attribute has been removed from all elements except topic, and the reifies attribute has been added on some elements.
- The itemIdentity, subjectLocator, and subjectIdentifier elements have been added.
- The subjectIndicatorRef and resourceRef elements have been removed.
- XTM no longer uses XLink and XML Base.
- The mergeMap element must now come before all topic and association elements.
- The datatype attribute has been added to resourceData, which also now supports embedded markup.

Annex A (informative)

Subject identifiers for defined terms

This annex defines one subject identifier for each formally defined term in Clause 3. The subject identifiers are defined for the sole purpose of enabling unambiguous reference to the subjects they identify, for example in order to enable the collation of information about those subjects. This part of ISO/IEC13250 attaches no processing semantics of any kind to these identifiers, over and above those associated with subject identifiers in general.

XTM

<http://psi.topicmaps.org/iso13250/glossary/XTM>

Bibliography

- [1] *T o p i c M a p s*, 2 0 0 3 , a v a i l a b l e a t <
http://www.y12.doe.gov/sgml/sc34/document/0322_files/iso13250-2nd-ed-v2.pdf>
- [2] *Topic Maps — Canonicalization*, available at <<http://www.isotopicmaps.org/sam/cxtm/>>
- [3] *XML Topic Maps (XTM) 1.0 Specification*, Steve Pepper, Graham Moore, TopicMaps.Org, 2001, available at <<http://www.topicmaps.org/xtm/1.0/>>